

TR 393 - Fiche de données



Description

TR 393 a été spécialement conçu pour les presses à paille, les épandeurs et l'outillage agricole sur et hors route. Le dessin particulier de la bande de roulement assure des extraordinaires capacités de flottaison et d'auto-nettoyage, en plus d'une longue durée de vie. Grâce à la large zone de contact, TR 393 fournit une excellente traction et minimise le compactage du sol.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Presse à paille • Outillage agricole • Épandeur

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
16.5L - 16.1 SL	STANDARD	I2	128 B	6	W14C	W14CH	420	1025	461	2966	TL	E11-106R-007109
21.5L - 16.1 SL	STANDARD	I2	146 B	10	W 18 CH	W 16 CH	546	1154			TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..