

TRAC FARM PLUS - Spécifications techniques



Description

TRAC FARM PLUS est un pneu arrière pour tracteurs spécialement conçu pour les applications de travail de la terre et de transport. Ce pneu se distingue de par une bande de roulement plus profonde avec pavés à deux angles afin de garantir tant une excellente traction qu'une conduite confortable sur la route. Le dessin spécial de la bande de roulement offre un contact plus large pour une meilleure stabilité et des propriétés d'auto-nettoyage extraordinaires. TRAC FARM PLUS allonge le cycle de vie du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	16.9 - 30
LI/SS	140 A8

Dimensions US Standard

Usa code	94046119
Ply Rating	12
Section Width (inch)	17.3
Overall Diameter (inch)	58.1
Static Loaded Radius (inch)	26.7
Rolling Circumference (inch)	175.8
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004529
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..