

TRAC GRADER + - Fiche de données



Description

TRAC GRADER + (G-2) est un pneu à construction diagonale pour niveleuses, il représente un excellent choix pour les clients dont la priorité est le budget. La carcasse résistante est conçue pour résister au temps. Le dessin auto-nettoyant de la bande de roulement montre une proportion crampon-espace qui fournit la meilleure traction dans toutes les conditions. La version spéciale est réalisée dans un mélange spécial, résistant aux coupures et déchirures.

UM

US Standard

Construction

❖ BIAS

Machinery

OTR: Niveleuse

| SIZE | Version | USACode | TRA Code | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | Tread Depth | ECE |
|------------|----------|----------|----------|----|-------------|--|------|------|------|-------|------|-------------|-----------------|
| 13.00 - 24 | SPECIAL | 94014668 | G2 | 12 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 13.4 | 50.4 | 23.6 | 155.2 | TL | 32 | |
| 13.00 - 24 | STANDARD | 94014545 | G2 | 12 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 13.4 | 50.4 | 23.6 | 155.2 | TL | 32 | E11-106R-003629 |
| 13.00 - 24 | STANDARD | 94014569 | G2 | 14 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 13.4 | 50.4 | 23.6 | 155.2 | TL | 32 | E11-106R-003630 |
| 13.00 - 24 | STANDARD | 94014583 | G2 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 13.4 | 50.4 | 23.6 | 155.2 | TL | 32 | |
| 14.00 - 24 | SPECIAL | 94014699 | G2 | 12 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC; 10.00 WA SDC | 14.3 | 53.1 | 23.5 | 157.1 | TL | 32 | |
| 14.00 - 24 | SPECIAL | 94014712 | G2 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 14.3 | 53.1 | 23.5 | 157.1 | TL | 32 | E11-106R-003632 |
| 14.00 - 24 | STANDARD | 94014606 | G2 | 12 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00 VA SDC; 10.00 WA SDC | 14.3 | 53.1 | 23.5 | 157.1 | TL | 32 | |
| 14.00 - 24 | STANDARD | 94014644 | G2 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 14.3 | 53.1 | 23.5 | 157.1 | TL | 32 | |
| 14.00 - 24 | STANDARD | 94059751 | G2 | 12 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00 VA SDC; 10.00 WA SDC | 14.3 | 53.1 | 23.5 | 157.1 | TT | 32 | |
| 14.00 - 24 | STANDARD | 94059768 | G2 | 16 | 8.00 TG SDC | 9.00/1.5 (DC) ; 10.00/VA SDC | 14.3 | 53.1 | 23.5 | 157.1 | TT | 32 | |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 14:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..