

V-FLEXA - Spécifications techniques



Description

V-FLEXA est un pneu radial spécialement conçu pour les remorques agricoles. C'est un produit Flotation de dernière génération doté de la technologie VF, qui permet de transporter des charges lourdes tant aux champs que sur la route avec une pression de gonflage inférieure de 30% par rapport à celle d'un pneu standard de même taille. Des ceintures en acier confèrent à la carcasse une plus grande résistance aux agressions. V-FLEXA non seulement supporte des charges lourdes en toute sécurité, mais il évite aussi le compactage du sol grâce à la parfaite répartition du poids. De plus, V-FLEXA a d'excellentes propriétés d'auto-nettoyage, une longue durabilité et une faible résistance au roulement.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Remorque

Version	STEEL BELTED
Type	TL
Tyre Size	VF 560/60 R 22.5
LI/SS	166 D

Dimensions International Standard

Section Width (mm)	555
Overall Diameter (mm)	1250
Static Loaded Radius (mm)	550
Rolling Circumference (mm)	3756
SRI (mm)	600
Rim Rec	AG 16.00
ECE	E11-106R-006763

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2
70	2075	2655	3185	3670	3910	4440	4825
65	2280	2915	3500	4030	4295	4880	5300
50	2670	3415	4100	4720	5030	5710	6205
40	2945	3765	4515	5200	5545	6295	6840
10	3740	4785	5740	6610	7045	8000	8695

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..