

V-FLEXA - Spécifications techniques



Description

V-FLEXA est un pneu radial spécialement conçu pour les remorques agricoles. C'est un produit Flotation de dernière génération doté de la technologie VF, qui permet de transporter des charges lourdes tant aux champs que sur la route avec une pression de gonflage inférieure de 30% par rapport à celle d'un pneu standard de même taille. Des ceintures en acier confèrent à la carcasse une plus grande résistance aux agressions. V-FLEXA non seulement supporte des charges lourdes en toute sécurité, mais il évite aussi le compactage du sol grâce à la parfaite répartition du poids. De plus, V-FLEXA a d'excellentes propriétés d'auto-nettoyage, une longue durabilité et une faible résistance au roulement.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Remorque

Version	STEEL BELTED
Type	TL
Tyre Size	VF 600/65 R 26.5
LI/SS	172 D

Dimensions US Standard

Usa code	94066056
Section Width (inch)	24.2
Overall Diameter (inch)	57.2
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	172.3
Rim Rec	AG20.00
ECE	E11-106R-006624

Load capacity (lbs)

mph / psi	12	17	23	29	35	41
45	5450	6960	8480	9620	11140	12650
40	5980	7640	9320	10560	12230	13890
30	7000	8960	10910	12360	14310	16260
25	7720	9870	12020	13630	15780	17930
5	9800	12540	15270	17320	20050	22790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..