

## XL GRIP (E3) - Spécifications techniques



### Description

XL GRIP (E-3) est un pneu à construction diagonale pour tombereaux rigides conçu pour minimiser les coupures et les crevaisons dans les conditions les plus sévères qui demandent une excellente traction. Ces caractéristiques se traduisent par un cycle de vie plus long du pneu.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Tombereau rigide

Version	STANDARD
Type	TT
Tyre Size	18.00 - 25

## Dimensions US Standard

Usa code	94015764
Ply Rating	32
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3/L3
Tread Depth	40

## Load capacity (lbs)

mph / psi	83	109
30	19300	-
5	-	33100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..