

XL GRIP IND3 (ECH) - Fiche de données



Description

XL GRIP (IND-3) est un pneu à construction diagonale pour les applications d'empilement et de levage. Ce pneu est caractérisé par une carcasse robuste qui se traduit par une grande durabilité ainsi qu'une stabilité élevée lors des opérations de levage.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 - 24	INDUSTRIAL	94032785	IND3	24	8.5	8.0	12.6	49.2	23	146.1	TT
16.00 - 25	INDUSTRIAL	94031894	IND3	28	11.25/2.0	13.00/2.0	18.3	58.5	26.9	173	TL
18.00 - 25	PORT INDUSTRIAL	94049035	IND3	32	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL
18.00 - 25	PORT INDUSTRIAL	94049042	IND3	40	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 10:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..