

XL GRIP IND3 (RTG) - Spécifications techniques



Description

XL GRIP (IND-3) est un pneu à construction diagonale pour les grues portiques RTG dans les applications de empilement et de levage. Ce pneu est caractérisé par une carcasse robuste réalisée avec un mélange de la bande de roulement élaboré à cet effet, ce qui se traduit par un cycle de vie plus long du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Grue RTG

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94015931
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND3

Load capacity (lbs)

mph / psi	145
5	50600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..