

## XL GRIP IND3 (RTG) - Spécifications techniques



### Description

XL GRIP (IND-3) est un pneu à construction diagonale pour les grues portiques RTG dans les applications de empilement et de levage. Ce pneu est caractérisé par une carcasse robuste réalisée avec un mélange de la bande de roulement élaboré à cet effet, ce qui se traduit par un cycle de vie plus long du pneu.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Grue RTG

|           |            |
|-----------|------------|
| Version   | INDUSTRIAL |
| Type      | TL         |
| Tyre Size | 21.00 - 35 |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Ply Rating                 | 36        |
| Overall Width (mm)         | 580       |
| Overall Diameter (mm)      | 2020      |
| Static Loaded Radius (mm)  | 928       |
| Rolling Circumference (mm) | 5980      |
| Rim Rec                    | 15.00/3.0 |
| TRA Code                   | IND3      |

## Load capacity (Kg)

|            |       |
|------------|-------|
| km/h / bar | 9.00  |
| 10         | 31000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..