

XL GRIP PLUS - Spécifications techniques



Description

XL GRIP PLUS (L-4) a été spécialement conçu pour les chargeuses. La bande de roulement profonde assure une excellente résistance aux coupures et crevaisons ainsi qu'un cycle de vie plus long du pneu. XL GRIP PLUS convient tout particulièrement pour les opérations de service pénible.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: Bulldozer • Chargeur

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	760
Overall Diameter (mm)	1915
Static Loaded Radius (mm)	876
Rolling Circumference (mm)	5709
Rim Rec	25.00/3.5
TRA Code	L4
Tread Depth	60

Load capacity (Kg)

km/h / bar	4.25
10	17500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 10:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..