

XL GRIP PLUS - Fiche de données



Description

XL GRIP PLUS (L-4) a été spécialement conçu pour les chargeuses. La bande de roulement profonde assure une excellente résistance aux coupures et crevaisons ainsi qu'un cycle de vie plus long du pneu. XL GRIP PLUS convient tout particulièrement pour les opérations de service pénible.

UM

US Standard

Construction

✚ BIAS

Machinery

OTR: Bulldozer • Chargeur

| SIZE | Version | USACode | TRA Code | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type | Tread Depth |
|------------|----------|----------|----------|----|-----------|---------|------|------|------|-------|------|-------------|
| 26.5 - 25 | STANDARD | 94033331 | L4 | 28 | 22.00/3.0 | | 27.2 | 69.9 | 32.1 | 206.8 | TL | 72 |
| 26.5 - 25 | STANDARD | 94044856 | L4 | 32 | 22.00/3.0 | | 27.2 | 69.9 | 32.1 | 206.8 | TL | 72 |
| 29.5 - 25 | STANDARD | 94033584 | L4 | 28 | 25.00/3.5 | | 29.9 | 75.4 | 34.5 | 224.8 | TL | 75 |
| 29.5 - 25 | STANDARD | 94044863 | L4 | 32 | 25.00/3.5 | | 29.9 | 75.4 | 34.5 | 224.8 | TL | 75 |
| 29.5 - 25 | STANDARD | 94059577 | L4 | 36 | 25.00/3.5 | | 29.9 | 75.4 | 34.5 | 224.8 | TL | 75 |
| 35/65 - 33 | STANDARD | 94064762 | L4 | 42 | 28.00/3.5 | | 35.4 | 81.9 | 0 | 0 | TL | 79 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 00:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..