

XL GRIP (SCRAPER) - Spécifications techniques



Description

XL GRIP (SCRAPER) est un pneu large non directionnel adapté pour les décapeuses sur n'importe quel terrain. Ce pneu est caractérisé par une carcasse robuste et par un mélange spécial qui garantissent une excellente résistance aux coupures et crevaisons ainsi que durabilité et traction extraordinaires même dans les conditions de service les plus sévères. Les autres avantages sont des propriétés élevées d'auto-nettoyage et une stabilité exceptionnelle.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Décapeuse

Version	STANDARD
Type	TL
Tyre Size	33.25 - 29

Dimensions US Standard

Usa code	94055487
Ply Rating	32
Overall Width (inch)	33.9
Overall Diameter (inch)	83.5
Rim Rec	27.00/3.5
Rim Alt	26.00/3.5
TRA Code	E3
Tread Depth	58

Load capacity (lbs)

mph / psi	47	65
30	33100	-
5	-	52000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 13:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..