

AGRIMAX ELOS - Specifiche tecniche



Description

AGRIMAX ELOS è stato progettato per esprimere la massima trazione anche in condizioni d'uso particolarmente problematiche su terreni bagnati – ad esempio risaie – e paludosi. Il disegno del battistrada è stato specificatamente studiato per garantire ottime qualità di autopulitura, un aspetto essenziale nei lavori sui campi fangosi e durante i trasferimenti. Per ottimizzare la produttività dell'azienda agricola, nel design dello pneumatico Agrimax Elos sono stati integrati dei cordoli di protezione sui fianchi per assicurare in ogni momento la massima protezione da possibili danneggiamenti.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	380/85 R 38 (14.9 R 38)
LI/SS	139 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1662
Static Loaded Radius (mm)	772
Rolling Circumference (mm)	4994
SRI (mm)	775
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-000779
TRA Code	R2

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1340	1560	1775	1995	2215	2430
40	1340	1560	1775	1995	2215	2430
30	1435	1670	1905	2140	2375	2605
10 LT	1795	2090	2380	2675	2970	3260
10 HT	1435	1670	1905	2140	2375	2605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 21:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..