

## AGRIMAX ELOS - Specifiche tecniche



### Description

AGRIMAX ELOS è stato progettato per esprimere la massima trazione anche in condizioni d'uso particolarmente problematiche su terreni bagnati – ad esempio risaie – e paludosi. Il disegno del battistrada è stato specificatamente studiato per garantire ottime qualità di autopulitura, un aspetto essenziale nei lavori sui campi fangosi e durante i trasferimenti. Per ottimizzare la produttività dell'azienda agricola, nel design dello pneumatico Agrimax Elos sono stati integrati dei cordoli di protezione sui fianchi per assicurare in ogni momento la massima protezione da possibili danneggiamenti.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	167A8/B

## Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1988
Static Loaded Radius (mm)	920
Rolling Circumference (mm)	6095
SRI (mm)	925
Rim Rec	DW 16 L
Rim Alt	DD 18 L ; DW 18 L
ECE	E11-106R-0010146
TRA Code	R2

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2	2.4	2.8	3.2
50	2130	2510	2890	3220	3600	3925	4310	4745	5125	5450
40	2130	2510	2890	3220	3600	3925	4310	4745	5125	5450
30	2280	2685	3095	3445	3855	4205	4610	5080	5485	5835
10 LT	2850	3365	3875	4310	4825	5260	5775	6360	6870	7305
10 HT	2280	2685	3095	3445	3855	4205	4610	5080	5485	5835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..