

AGRIMAX ELOS - Scheda tecnica



Description

AGRIMAX ELOS è stato progettato per esprimere la massima trazione anche in condizioni d'uso particolarmente problematiche su terreni bagnati – ad esempio risaie – e paludosi. Il disegno del battistrada è stato specificatamente studiato per garantire ottime qualità di autopulitura, un aspetto essenziale nei lavori sui campi fangosi e durante i trasferimenti. Per ottimizzare la produttività dell'azienda agricola, nel design dello pneumatico Agrimax Elos sono stati integrati dei cordoli di protezione sui fianchi per assicurare in ogni momento la massima protezione da possibili danneggiamenti.

UM

US Standard

Construction



RADIAL

Machinery

Agricoltura: Trattore

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
420/85 R 28 (16.9 R 28)	STANDARD	94040810	R2	139 A8/B	W 15 L	W 13 ; W 14 L	17.2	57.8	26.2	171.2	TL	E4-106R-000768
480/70 R 34	STANDARD	94070299	R2	155 A8/155 B	W 15 L	W 16 L ; W 14 L	19.7	63.2	28.9	191.7	TL	E11-106R-007532
340/85 R 38 (13.6 R 38)	STANDARD	94040452	R2	133 A8/B	W 12	W 11	13.9	63.1	28.9	188	TL	E4-106R-001477
380/85 R 38 (14.9 R 38)	STANDARD	94036134	R2	139 A8/B	W 12	W 11 ; W 13	15	65.4	30.4	196.6	TL	E4-106R-000779
420/85 R 38 (16.9 R 38)	STANDARD	94034512	R2	144 A8/B	W 15 L	W 13 ; W 14 L	17.2	68.3	30.9	202.2	TL	E4-106R-000780
480/80 R 38 (18.4 R 38)	STANDARD	94053766	R2	149 A8/B	W 16 L	W 15 L ; DW 16 L	19.3	71	32.3	210.9	TL	E11-106R-002991
710/70 R 38	STANDARD	94058617	R2	178 A8/B	DW 23 B	DW 25 B	28.2	79.5	36	240.3	TL	E11-106R-004896
480/80 R 42 (18.4 R 42)	STANDARD	94040827	R2	151 A8/B	DW 16 L	DD 16 L ; W 16 L	19.3	74.4	33.7	221.6	TL	E4-106R-001481
520/85 R 42 (20.8 R 42)	STANDARD	94040834	R2	157 A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	35.6	230.9	TL	E4-106R-000793
520/85 R 42 (20.8 R 42)	STANDARD	94075850	R2	167A8/B	DW 16 L	DD 18 L ; DW 18 L	20.3	78.3	36.2	240	TL	E11-106R-0010146
520/85 R 46	STANDARD	94070503	R2	169 A8/169 B	DW 16 L	DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W18 L ; DD 16 L ; DD 18 L	20.9	81.7	37.7	247.8	TL	E11-106R-007935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..