

AGRIMAX FORCE - Scheda tecnica



Description

AGRIMAX FORCE, il prodotto di punta di BKT, è uno pneumatico radiale appositamente progettato per la lavorazione del terreno e le applicazioni di trasporto e raccolta con trattori e mietitrici ad alta potenza, garantendo massime prestazioni ed efficienza. Grazie alla tecnologia IF, questo pneumatico è in grado di trasportare carichi pesanti con una pressione di gonfiaggio inferiore rispetto a uno pneumatico standard riducendo la compattazione del suolo. AGRIMAX FORCE è caratterizzato da un tallone rinforzato e offre eccellente trazione, ottime proprietà di autopulitura e consumi ridotti oltre ad un'esperienza di guida confortevole.

UM

International Standard

Construction



RADIAL

Machinery

Agricoltura: Mietitrebbia • Trattore a elevata potenza

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
IF 600/70 R 28	STANDARD	R1W	164 D	DW 21 B	DW 20 B	603	1551	694	4654	725	TL	E4-106R-000795
IF 710/55 R 28 CFO	STANDARD	R1W	165 D	DW 25 B		716	1493	663	4442	700	TL	E11-106R-005498
IF 600/70 R 30 CFO	SPECIAL	R1W	165 D	DW 21 B ; DW 21 A	DW 20 A ; DW 20 B	603	1602	708	4800	750	TL	E11-106R-006495
IF 600/70 R 30 CFO	STANDARD	R1W	165 D	DW 21 B ; DW 21 A	DW 20 A ; DW 20 B	603	1602	708	4800	750	TL	E11-106R-006495
IF 620/75 R 30 CFO	STANDARD	R1W	169 D	DW 23 B	DW 21 B	650	1703	759	5100	800	TL	E11-106R-006496
IF 710/60 R 30 CFO	STANDARD	R1W	168 D	DW 25 B		708	1614	714	4814	775	TL	E4-106R-001407
IF 710/55 R 30 CFO	STANDARD	R1W	166 D	DW 25 B		716	1544	686	4616	725	TL	E11-106R-005716
IF 600/70 R 34	STANDARD	R1W	167 D	DW 21 B ; DW 21 A	DW 20 A ; DW 20 B	603	1704	757	5070	800	TL	E4-106R-001408
IF 650/60 R 34	STANDARD	R1W	165 D	DW 23 B	DW 21 B	650	1644	746	4954	775	TL	E11-106R-006014
IF 650/65 R 34 CFO	SPECIAL	R1W	161 D	DW 23 B	DW 20 B	650	1710	764	5078	825	TL	E4-106R-001826
IF 650/65 R 34 CFO	STANDARD	R1W	161 D	DW 23 B	DW 20 B	650	1710	764	5078	825	TL	E4-106R-001826
IF 710/55 R 34 CFO	STANDARD	R1W	170 D	DW 25 B		716	1646	746	4962	775	TL	E11-106R-005995
IF 710/60 R 34 CFO	SPECIAL	R1W	170 D	DW 25 B		708	1716	763	5126	825	TL	E4-106R-001485
IF 710/60 R 34 CFO	STANDARD	R1W	170 D	DW 25 B		708	1716	763	5126	825	TL	E4-106R-001485
IF 710/75 R 34 CFO	STANDARD	R1W	178 D	DW 25 B	DW 23 B	716	1929	870	5775	900	TL	E11-106R-003017
IF 380/80 R 38	STANDARD	R1W	149 D	W 12	W 11 ; W 13	380	1573	725	4793	750	TL	E11-106R-005715
IF 420/85 R 38	STANDARD	R1W	155 D	DW 14 L	DW 15 L	419	1670	780	5017	800	TL	E11-106R-004897
IF 650/65 R 38 CFO	STANDARD	R1W	169 D	DW 23 B		650	1830	830	5510	875	TL	E11-106R-005103
IF 650/75 R 38 CFO	SPECIAL	R1W	175 D	DW 23 B	DW 21 B	651	1941	866	5802	925	TL	E11-106R-007385
IF 650/75 R 38 CFO	STANDARD	R1W	175 D	DW 23 B	DW 21 B	651	1941	866	5802	925	TL	E11-106R-007385
IF 650/85 R 38 CFO	STANDARD	R1W	179 D	DW 23 B	DW 20 B ; DW 21 B	663	2071	927	6106	975	TL	E4-106R-002649
IF 710/60 R 38	STANDARD	R1W	172 D	DW 25 B		708	1817	812	5405	875	TL	E11-106R-004754
IF 800/70 R 38 CFO	STANDARD	R1W	184 D	DW 27 B	DW 25 B, DW 28 B, DW 30 B	794	2085	923	6184	975	TL	E11-106R-006497
IF 900/60 R 38 CFO	STANDARD	R1W	184 D	DW 30 A ; DW 30 B	TW 31 B	916	2045	904	6107	975	TL	E11-106R-006493
IF 650/85 R 42 CFO	STANDARD	R1W	180 D	DW 23 B		650	2173	965	6400	1025	TL	E4-106R-001832
IF 710/70 R 42 CFO	SPECIAL	R1W	179 D	DW 25 B	DW 23 B	716	2061	919	6168	975	TL	E4-106R-001830
IF 710/70 R 42 CFO	STANDARD	R1W	179 D	DW 25 B	DW 23 B	716	2061	919	6168	975	TL	E4-106R-001830
IF 710/75 R 42 CFO	SPECIAL	R1W	181 D	DW 25 B	DW 23 B	716	2133	967	6403	1000	TL	E11-106R-006490
IF 710/75 R 42 CFO	STANDARD	R1W	181 D	DW 25 B	DW 23 B	716	2133	967	6403	1000	TL	E11-106R-006490
IF 800/70 R 42	STANDARD	R1W	186	DW 27 B	DW 25 B, DW 28 B, DW	794	2150	950	6400	1025	TL	E4-106R-

CFO			D	30 B								002650	
IF 800/70 R 42 CFO	STANDARD	R1W	192 D	DW 27 B	DW 25 B, DW 28 B, DW 30 B	794	2150	950	6400	1025	TL	E11-106R-006481	
IF 900/50 R 42 CFO	STANDARD	R1W	180 D	DW 30 B	TW 30 B	881	1955	872	5830	950	TL	E11-106R-006492	
IF 900/60 R 42 CFO	STANDARD	R1W	186 D	DW 30 B	TW 30 B	916	2147	950	6416	1025	TL	E11-106R-006494	
IF 750/75 R 46 CFO	STANDARD	R1W	186 D	DW 25 B		742	2294	1032	6802	1075	TL	E11-106R-006491	
IF 480/95 R 50	STANDARD	R1W	170 D	DW 16 B		479	2170	1002	6574	1025	TL	E11-106R-004898	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 04:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..