

## AGRIMAX RT 600 - Specifiche tecniche

### Description

AGRIMAX RT 600 è lo pneumatico ideale per manti erbosi e le applicazioni di raccolto e irrorazione. Grazie alla sua ampia area di contatto, AGRIMAX RT 600 garantisce una distribuzione di pressione ottimizzata sul terreno riducendo i danni sul manto erboso e proteggendo il terreno. Grazie alla sua tecnologia a spalla tonda, al tallone rinforzato e al maggior numero di ramponi, lo pneumatico garantisce grande stabilità e trazione.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Mietitrebbia • Spargitore • Trattore



|           |                             |
|-----------|-----------------------------|
| Version   | STANDARD                    |
| Type      | TL                          |
| Tyre Size | 800/65 R 32<br>(30.5L R 32) |
| LI/SS     | 181 A8/178 B                |

# Dimensions International Standard

|                            |                   |
|----------------------------|-------------------|
| Section Width (mm)         | 775               |
| Overall Diameter (mm)      | 1820              |
| Static Loaded Radius (mm)  | 823               |
| Rolling Circumference (mm) | 5558              |
| SRI (mm)                   | 875               |
| Rim Rec                    | DW 27 B           |
| Rim Alt                    | DH 27 B ; DW 25 B |
| ECE                        | E4-106R-001429    |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4   | 2.8   | 3.2   | 3.6   | 4.0   | 4.4   |
|------------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 50         | 3175 | 3660 | 4485 | 4900 | 5385 | 5865  | 6350  | 6900  | 7500  | -     | -     |
| 40         | 3450 | 3975 | 4875 | 5325 | 5850 | 6375  | 6900  | 7500  | 8250  | -     | -     |
| 30         | 3695 | 4255 | 5220 | 5700 | 6260 | 6825  | 7385  | 8025  | 8830  | -     | -     |
| 10 LT      | 4625 | 5330 | 6535 | 7140 | 7840 | 8545  | 9250  | 10050 | 11055 | -     | -     |
| 10 HT      | 3695 | 4255 | 5220 | 5700 | 6260 | 6825  | 7385  | 8025  | 8830  | -     | -     |
| 10 Cyc     | -    | 5655 | 7230 | 7960 | 9250 | 10140 | 11055 | 12025 | 12440 | 13000 | 14000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 22:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..