

AGRIMAX RT 600 - Specifiche tecniche

Description

AGRIMAX RT 600 è lo pneumatico ideale per manti erbosi e le applicazioni di raccolto e irrorazione. Grazie alla sua ampia area di contatto, AGRIMAX RT 600 garantisce una distribuzione di pressione ottimizzata sul terreno riducendo i danni sul manto erboso e proteggendo il terreno. Grazie alla sua tecnologia a spalla tonda, al tallone rinforzato e al maggior numero di ramponi, lo pneumatico garantisce grande stabilità e trazione.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Mietitrebbia • Spargitore • Trattore



Version	STANDARD
Type	TL
Tyre Size	800/65 R 32 (30.5L R 32)
LI/SS	176 A8/173 B

Dimensions US Standard

Usa code	94044795
Section Width (inch)	30.5
Overall Diameter (inch)	71.7
Static Loaded Radius (inch)	32.4
Rolling Circumference (inch)	218.8
Rim Rec	DW 27 B
Rim Alt	DH 27 B ; DW 25 B
ECE	E4-106R-001428

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	44	46	52
30	7000	8070	9890	10800	11870	12930	14000	14330	-	-
25	7610	8760	10750	11740	12900	14050	15210	15650	-	-
20	8150	9380	11510	12570	13800	15050	16280	16750	-	-
5 LT	10200	11750	14410	15740	17280	18840	20390	20980	-	-
5 HT	8150	9380	11510	12570	13800	15050	16280	16750	-	-
5 Cyc.	-	12470	15940	17550	20390	22350	24370	25440	26510	27420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..