

AGRIMAX RT 657 - Specifiche tecniche



Description

AGRIMAX RT 657 è lo pneumatico ideale per la lavorazione del terreno e per l'utilizzo sulla strada; alcune misure sono anche idonee per la vendemmia. Lo pneumatico assicura un eccellente comfort di guida nonché risparmi significativi di carburante. Agrimax RT 657 è la scelta migliore per chi ha bisogno di uno pneumatico versatile e affidabile senza compromettere le performance.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore • Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	600/65 R 34
LI/SS	157 D/160 A8

Dimensions US Standard

Usa code	94032327
Section Width (inch)	24.1
Overall Diameter (inch)	64.7
Static Loaded Radius (inch)	29.2
Rolling Circumference (inch)	195.3
Rim Rec	DW 20 B
Rim Alt	W 18 L
ECE	E4-106R-001405
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4360	5090	5730	6370	7010	7550	8370	9100
30	4600	5360	6030	6690	7360	7940	8800	9560
25	4760	5560	6250	6940	7640	8230	9130	9920
20	5030	5860	6590	7330	8060	8690	9630	10460
5 LT	5850	6830	7680	8540	9390	10120	11220	12190
5 HT	5030	5860	6590	7330	8060	8690	9630	10460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..