

AGRIMAX RT 765 - Specifiche tecniche



Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore •
Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	260/70 R 16
LI/SS	109 A8/B

Dimensions US Standard

Usa code	94021888
Section Width (inch)	10.2
Overall Diameter (inch)	30.3
Static Loaded Radius (inch)	13.6
Rolling Circumference (inch)	89.9
Rim Rec	W 8
Rim Alt	W 8 L ; W 9 L
ECE	E4-106R-000610
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1070	1230	1410	1600	1770	1960	2120	2270
25	1070	1230	1410	1600	1770	1960	2120	2270
20	1150	1320	1520	1710	1910	2110	2270	2440
5 LT	1430	1650	1900	2140	2380	2620	2830	3040
5 HT	1150	1320	1520	1710	1910	2110	2270	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..