

## AGRIMAX RT 765 - Specifiche tecniche



### Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agricoltura: Macchina irroratrice • Trattore •  
Vendemmiatrice

|           |             |
|-----------|-------------|
| Version   | SPECIAL     |
| Type      | TL          |
| Tyre Size | 420/70 R 24 |
| LI/SS     | 134 D       |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| TKPH                       | 1               |
| Section Width (mm)         | 418             |
| Overall Diameter (mm)      | 1248            |
| Static Loaded Radius (mm)  | 554             |
| Rolling Circumference (mm) | 3680            |
| SRI (mm)                   | 600             |
| Rim Rec                    | W 13            |
| Rim Alt                    | W 12 ; W 14 L   |
| ECE                        | E11-106R-005825 |
| TRA Code                   | R1W             |

## Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  |
|------------|------|------|------|------|------|------|------|
| 65         | 1060 | 1230 | 1400 | 1590 | 1760 | 1930 | 2120 |
| 50         | 1115 | 1295 | 1475 | 1675 | 1855 | 2030 | 2230 |
| 40         | 1165 | 1350 | 1535 | 1745 | 1930 | 2120 | 2325 |
| 30         | 1220 | 1420 | 1615 | 1830 | 2030 | 2225 | 2440 |
| 10 LT      | 1425 | 1655 | 1880 | 2135 | 2365 | 2590 | 2845 |
| 10 HT      | 1220 | 1420 | 1615 | 1830 | 2030 | 2225 | 2440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..