

AGRIMAX RT 765 - Specifiche tecniche



Description

AGRIMAX RT 765, uno pneumatico della serie 70 di BKT, è ideale per equipaggiare i trattori più moderni impegnati in applicazioni pesanti, quali lavorazioni del terreno, spostamenti su campo e su strada, la vendemmia e irrorazioni. L'ampia area di contatto garantisce la migliore trazione e ottimo comfort su tutte le superfici in qualsiasi momento. Questo pneumatico offre elevate proprietà di autopulitura e assicura una compattazione del suolo ridotta. Sono disponibili due misure dotate di tecnologia con cinture in acciaio.

UM

US Standard

Construction



RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore •
Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	520/70 R 34
LI/SS	148 D

Dimensions US Standard

Usa code	94063079
Section Width (inch)	20.3
Overall Diameter (inch)	64.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	194
Rim Rec	W 16 L
Rim Alt	W 15 L ; W 18 L
ECE	E11-106R-005831
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	3820	4450	5070	5700	6330	6940
30	4020	4670	5330	5990	6920	7300
25	4190	4870	5560	6240	6920	7610
20	4400	5110	5840	6560	7270	7990
5 LT	5130	5960	6800	7640	8480	9310
5 HT	4400	5110	5840	6560	7270	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..