

AGRIMAX RT 855 - Specifiche tecniche



Description

AGRIMAX RT 855 si distingue per l'eccellente trazione e il comfort. Principalmente sviluppato per la lavorazione del terreno e il trasporto sia su campo che sulla strada, alcune misure sono anche idonee per applicazioni di irrorazione e vendemmia. AGRIMAX RT 855 possiede ottime doti di autopulitura che consentono il rapido cambio dalle operazioni sul campo all'impiego su strada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore •
Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	480/80 R 50 (18.4 R 50)
LI/SS	159 A8/B

Dimensions International Standard

Section Width (mm)	489
Overall Diameter (mm)	2036
Static Loaded Radius (mm)	941
Rolling Circumference (mm)	6183
SRI (mm)	975
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; W 15 L
ECE	E4-106R-001486
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	2060	2365	2715	3065	3415	3765	4070	4375
40	2060	2365	2715	3065	3415	3765	4070	4375
30	2205	2530	2905	3280	3655	4030	4360	4685
10 LT	2760	3170	3640	4110	4575	5045	5455	5865
10 HT	2205	2530	2905	3280	3655	4030	4360	4685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..