

AGRIMAX RT 945 - Specifiche tecniche



Description

AGRIMAX RT 945 è stato particolarmente sviluppato per colture a filari: non danneggia le culture e protegge il raccolto. Inoltre, le straordinarie capacità di auto-pulitura consentono il rapido cambio dalle operazioni sul campo all'utilizzo sulla strada, dove AGRIMAX RT 945 dimostra performance brillanti. La sua carcassa resistente conferisce allo pneumatico ottima stabilità, trazione eccellente nonché durabilità straordinaria.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina irroratrice • Trattore

Version	STANDARD
Type	TL
Tyre Size	320/90 R 50 (12.4 R 50)
LI/SS	150 A8/B

Dimensions US Standard

Usa code	94037612
Section Width (inch)	12.6
Overall Diameter (inch)	72.7
Static Loaded Radius (inch)	34.4
Rolling Circumference (inch)	221.2
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E4-106R-000787
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
30	3110	4070	4950	5400	5760	6280	6800	7400	-
25	3110	4070	4950	5400	5760	6280	6800	7400	-
20	3330	4350	5300	5780	6170	6720	7270	7900	-
5	4320	5650	6880	7540	7980	8750	9530	10310	11080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 05:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..