

## AGRIMAX SPARGO - Specifiche tecniche



### Description

AGRIMAX SPARGO è lo pneumatico BKT specifico per applicazioni nelle colture in filari, progettato per aumentare la produttività del campo conservando il suolo nel lungo termine. Dotato di tecnologia VF, lo pneumatico offre una maggiore capacità di carico con gonfiaggio standard. Grazie alla carcassa robusta e il maggior numero di ramponi, AGRIMAX SPARGO garantisce eccellente durabilità abbinata ad una forte stabilità sia sul campo che durante gli spostamenti su strada.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Trattore

|           |                    |
|-----------|--------------------|
| Version   | STANDARD           |
| Type      | TL                 |
| Tyre Size | VF 320/90 R 54 CFO |
| LI/SS     | 168 D              |

## Dimensions International Standard

|                            |                               |
|----------------------------|-------------------------------|
| Section Width (mm)         | 323                           |
| Overall Diameter (mm)      | 1948                          |
| Static Loaded Radius (mm)  | 910                           |
| Rolling Circumference (mm) | 5946                          |
| SRI (mm)                   | 950                           |
| Rim Rec                    | W 11                          |
| Rim Alt                    | W 10 ; DW 10 ; W 10 L ; DW 11 |
| ECE                        | E11-106R-009070               |
| TRA Code                   | R1                            |

## Load capacity (Kg)

| km/h / bar    | 1.0  | 1.2  | 1.4  | 1.6  | 1.8  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  | 3.4  | 3.6  | 3.8  | 4.0  | 4.2  | 4.4  |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70            | 2230 | 2490 | 2800 | 3060 | 3215 | 3370 | 3475 | 3575 | 3760 | 3940 | 4095 | 4250 | 4380 | 4510 | 4640 | 4770 | 4975 | 5180 |
| From 65 to 40 | 2410 | 2690 | 3025 | 3305 | 3475 | 3640 | 3755 | 3865 | 4060 | 4260 | 4425 | 4595 | 4735 | 4875 | 5015 | 5155 | 5380 | 5600 |
| 30            | 2460 | 2745 | 3090 | 3375 | 3545 | 3715 | 3830 | 3945 | 4145 | 4345 | 4515 | 4690 | 4830 | 4975 | 5115 | 5260 | 5490 | 5715 |
| 20            | 2505 | 2800 | 3150 | 3440 | 3615 | 3790 | 3905 | 4020 | 4225 | 4430 | 4605 | 4780 | 4925 | 5070 | 5215 | 5360 | 5595 | 5825 |
| 10            | 2650 | 2960 | 3330 | 3635 | 3820 | 4005 | 4130 | 4255 | 4470 | 4685 | 4870 | 5055 | 5210 | 5360 | 5515 | 5670 | 5915 | 6160 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 19:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..