

AGRIMAX TURF RT 333 - Specifiche tecniche



Description

AGRIMAX TURF RT 333 (R-3 +) è uno pneumatico radiale progettato per piccoli trattori in applicazioni di giardinaggio, in vigneti e frutteti. Il suo design arrotondato fornisce bassa compattazione del terreno e lo rende estremamente delicato sul terreno. Il suo esclusivo battistrada extra profondo (R-3 +) e il design speciale con blocchi direzionali garantiscono un'eccellente trazione sia sul campo che su strada, nonché un ciclo di vita prolungato. AGRIMAX TURF RT 333 (R-3 +) garantisce grandi proprietà di autopulizia e, grazie alla sua bassa resistenza al rotolamento, consente un notevole risparmio di carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Macchina per il raccolto di frutteti • Trattorino
• Vendemmiatrice

Version	STANDARD
Type	TL
Tyre Size	320/70 R 20
LI/SS	113 A8/113 B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	982
Static Loaded Radius (mm)	441
Rolling Circumference (mm)	2916
SRI (mm)	450
Rim Rec	W10
Rim Alt	W9 ; W11
ECE	E11-106R-006944

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	635	740	840	945	1050	1150
40	635	740	840	945	1050	1150
30	680	795	905	1015	1125	1235
10 LT	850	990	1130	1270	1410	1545
10 HT	680	795	905	1015	1125	1235

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..