

## AGRIMAX TURF RT 333 - Scheda tecnica



### Description

AGRIMAX TURF RT 333 (R-3 +) è uno pneumatico radiale progettato per piccoli trattori in applicazioni di giardinaggio, in vigneti e frutteti. Il suo design arrotondato fornisce bassa compattazione del terreno e lo rende estremamente delicato sul terreno. Il suo esclusivo battistrada extra profondo (R-3 +) e il design speciale con blocchi direzionali garantiscono un'eccellente trazione sia sul campo che su strada, nonché un ciclo di vita prolungato. AGRIMAX TURF RT 333 (R-3 +) garantisce grandi proprietà di autopulizia e, grazie alla sua bassa resistenza al rotolamento, consente un notevole risparmio di carburante.

### UM

US Standard

### Construction



RADIAL

### Machinery

Agricoltura: Macchina per il raccolto di frutteti • Trattorino  
• Vendemmiatrice

| SIZE       | Version  | USACode  | TRA Code | LI/SS          | RIM REC | RIM ALT         | SW   | OD   | SLR  | RC    | Type | ECE              |
|------------|----------|----------|----------|----------------|---------|-----------------|------|------|------|-------|------|------------------|
| 220/55 R12 | STANDARD | 94070237 |          | 82 A8/B        | 7       |                 | 8.7  | 21.7 | 9.8  | 64.8  | TL   | E11-106R-007600  |
| 240/60 R12 | STANDARD | 94070657 |          | 89 A8/B        | 7       |                 | 9.5  | 23.3 | 10.6 | 70    | TL   | E11-106R-007679  |
| 215/65 R14 | STANDARD | 94076277 |          | 90 A8 / 90 B   | W 7     | W 6             | 8.7  | 24.8 | 11.4 | 75    | TL   | E11-106R-0010331 |
| 200/65 R16 | STANDARD | 94070640 |          | 94 A8/B        | W6      |                 | 8    | 26.2 | 12.2 | 78.7  | TL   | E11-106R-007678  |
| 200/70 R16 | STANDARD | 94074136 | R1W      | 94 A8/B        | W 6     |                 | 7.9  | 27   | 12.5 | 80.9  | TL   | E11-106R-008659  |
| 240/70 R16 | STANDARD | 94070282 |          | 104 A8/B       | W8      | W 8 L ; W 9     | 9.6  | 29.2 | 13.4 | 87.1  | TL   | E11-106R-007531  |
| 260/70 R16 | STANDARD | 94067909 |          | 109 A8/109 B   | W 8     | W 8 L ; W 9     | 10.2 | 30.3 | 13.7 | 90    | TL   | E11-106R-007158  |
| 280/70 R16 | STANDARD | 94065714 |          | 112 A8/112 B   | W9      | W 8 ; W 10      | 11.4 | 31.5 | 14.1 | 93.3  | TL   | E11-106R-006472  |
| 280/70 R18 | STANDARD | 94065707 |          | 114 A8/114 B   | W 9     | W 8 ; W 10      | 11.4 | 33.1 | 15.4 | 100.4 | TL   | E11-106R-006473  |
| 320/65 R18 | STANDARD | 94071081 |          | 109 A8/109 B   | W 10    | W 9 ; W 11      | 12.6 | 34.4 | 15.5 | 102   | TL   | E11-106R-007844  |
| 300/70 R20 | STANDARD | 9406748  |          | 110 A8/110 B   | W9      | W10             | 11.6 | 37.5 | 17   | 111.3 | TL   | E11-106R-006943  |
| 320/70 R20 | STANDARD | 94067558 |          | 113 A8/113 B   | W10     | W9 ; W11        | 12.6 | 38.7 | 17.4 | 114.8 | TL   | E11-106R-006944  |
| 380/70 R20 | STANDARD | 94068821 |          | 122 A8/122 B   | W 12    | W 11 ; W 13     | 15   | 42.6 | 19.1 | 126.5 | TL   | E11-106R-007111  |
| 360/70 R24 | STANDARD | 94067916 |          | 122 A8/122 B   | W 11    | W 10 ; W 12     | 14.1 | 45.4 | 20.4 | 134.2 | TL   | E11-106R-007110  |
| 380/70 R24 | STANDARD | 94068838 |          | 125 A8/125 B   | W 12    | W 11 ; W 13     | 15   | 46.9 | 21   | 139.3 | TL   | E11-106R-007112  |
| 420/70 R24 | STANDARD | 94069460 |          | 130 A8 / 130 B | W 13    | W 12 ; W 14 L   | 16.5 | 49.1 | 21.9 | 146.8 | TL   | E11-106R-007206  |
| 420/85 R24 | STANDARD | 94501649 |          | 137 A8 / 137 B | W 15 L  | DW15L;DW14L     | 17.1 | 52.1 | 23.4 | 155.8 | TL   | E11-106R-0010344 |
| 340/85 R28 | STANDARD | 94076390 |          | 127 A8 / 127 B | W 12    | W11;DW11;DW12   | 14.6 | 50.7 | 23   | 152.5 | TL   | E11-106R-0010343 |
| 480/70 R28 | STANDARD | 94075393 |          | 140 A8 / 140 B | W 15 L  | W 14 L ; W 16 L | 18.9 | 55.9 | 24.8 | 166.5 | TL   | E11-106R-009049  |
| 480/70 R30 | STANDARD | 94075409 |          | 141 A8 / 141 B | W 15 L  | W 14 L ; W 16 L | 18.9 | 58.2 | 26   | 173.1 | TL   | E11-106R-009050  |
| 480/70 R34 | STANDARD | 94075232 |          | 149 A8 / 149 B | W 15 L  | W 14 L ; W 16 L | 19.3 | 62.2 | 28.5 | 188.4 | TL   | E11-106R-009042  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 05:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..