

AIROMAX AM 543 - Specifiche tecniche



Description

AIROMAX AM 543 è lo pneumatico ideale per applicazioni con gru nel settore costruzioni. Lo pneumatico mostra eccellente trazione insieme ad elevata stabilità. Visto che gli pneumatici per gru sono soggetti a sollecitazioni e condizioni d'impiego estreme, AIROMAX AM 543 è stato progettato per fornire un'ottima resistenza al calore. Inoltre, è idoneo per tutte le operazioni in cui si richiede un elevato livello di manovrabilità.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Gru mobile

Version	STANDARD
Type	TL
Tyre Size	385/95 R 25 (14.00 R 25)
LI/SS	170 E

Dimensions International Standard

Overall Width (mm)	375
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4156
Rim Rec	10.00/1.5

Load capacity (Kg)

km/h / bar	9.00
70	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..