

ARROW - Specifiche tecniche



Description

ARROW è idoneo per applicazioni di trasporto con rimorchi. Lo pneumatico è stato sviluppato per un principale impiego su strada e assicura un chilometraggio migliore nonché un ciclo di vita prolungato dello pneumatico. ARROW offre un'elevata capacità di carico anche ad alta velocità. Una versione HD realizzata con mescola speciale è disponibile per gli utilizzatori che richiedono prestazioni avanzate.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	216
Overall Diameter (mm)	825
Rim Rec	6.00 G
Rim Alt	5.50 F

Load capacity (Kg)

km/h / bar	7.60
100 LS	1600
100 LD	1400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..