

AT 111 - Specifiche tecniche



Description

AT 111 è adatto per le competizioni sportive All Terrain con veicoli ATV. Per utilizzatori che hanno bisogno di maggiore durabilità e trazione, è disponibile una versione "HD" con battistrada profondo.

UM

International Standard

Construction



Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Туре	TL
Tyre Size	AT 19 X 6 - 10

Dimensions International Standard

Ply Rating	4
Section Width (mm)	152
Overall Diameter (mm)	472
Rim Rec	5.0

Load capacity (Kg)

km/h / bar	0.95
80	100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 10:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..