

AT 171 - Specifiche tecniche



Description

AT 171 è stato specificamente progettato per trattori per corse 4x4 nel fango. Il particolare disegno direzionale ed extra profondo del battistrada assicura eccellente trazione su superfici bagnate e fangose.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Veicolo ATV • Veicolo per corse nel fango

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | AT 35 X 9 - 20 |
| LI/SS | 85 A8 / 61 F |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94054329 |
| Ply Rating | 6 |
| Section Width (inch) | 7.9 |
| Overall Diameter (inch) | 35.2 |
| Static Loaded Radius (inch) | 16.5 |
| Rolling Circumference (inch) | 105.1 |
| Rim Rec | W 7 |
| Rim Alt | W 6 |
| TRA Code | R1W+ |

Load capacity (lbs)

| mph / psi | 20 | 15 |
|---------------------|------|-----|
| 25 MUD BOGGING | 1135 | - |
| 50 MUD BOGGING | 567 | - |
| 25 CASUAL TRANSPORT | - | 940 |
| 50 CASUL TRANSPORT | - | 481 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..