

AT 316 - Specifiche tecniche



Description

AT 316 è idoneo per trattori utilitari compatti nelle applicazioni municipalità e manutenzione. Il particolare disegno del battistrada assicura eccellente trazione senza compromettere la protezione del campo – una caratteristica essenziale per questo tipo di applicazione. Lo pneumatico AT 316 è anche disponibile in versione “aramid belted”, con cinture in aramide, che fornisce maggiore resistenza alla perforazione.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore compatto

Version	STANDARD
Type	TL
Tyre Size	24 X 12.00 - 12

Dimensions US Standard

Usa code	94001200
Ply Rating	4
Section Width (inch)	12.4
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.7
Rolling Circumference (inch)	69.6
Rim Rec	10.50 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-004082

Load capacity (lbs)

mph / psi	20
10	1710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 05:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..