

AW 09 - Specifiche tecniche



Description

AW 09 è stato sviluppato per lavorazioni del terreno, la raccolta del fieno e applicazioni di trasporto con attrezzi agricoli, presse per balle di fieno e rimorchi. È idoneo per essere impiegato nell'agricoltura moderna sia su strada che fuori strada. La carcassa rinforzata garantisce un'elevata capacità di carico nonché un ciclo di vita prolungato dello pneumatico. AW 09 è stato sviluppato con una particolare miscela resistente a tagli e lacerazioni che garantisce una straordinaria resistenza alle stoppie.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	300/80 - 15.3
LI/SS DRIVE WHEEL	120 A8
LI/SS FREE ROLLING	132 A8

Dimensions US Standard

Usa code	94037810
Section Width (inch)	11.6
Overall Diameter (inch)	33.9
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	99.2
Rim Rec	9.00
ECE	E4-106R-000375

Load capacity (lbs)

mph / psi	41
5 FR	6170
15 FR	5250
20 FR	4940
25 FR	4410
5 DW	4320
15 DW	3670
20 DW	3460
25 DW	3090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..