

AW 711 - Specifiche tecniche



Description

AW 711 è uno pneumatico radiale per attrezzature agricole, specificamente progettato per l'impiego nell'agricoltura moderna, e adatto per la lavorazione della terra. Grazie alla speciale miscela del battistrada, AW 711 assicura un lungo ciclo di vita del prodotto, sia se utilizzato su superfici morbide che su superfici dure. La bassa resistenza al rotolamento durante il trasferimento su strada garantisce risparmi significativi nel consumo di carburante. Grazie alla tecnologia VF, AW 711 è in grado di portare carichi pesanti a basse pressioni.

UM

International Standard

Construction



RADIAL

Machinery

Agricoltura: Mietitrebbia • Attrezzi agricoli

Version	STEEL BELTED
Type	TL
Tyre Size	VF 410/50 R 16.5
LI/SS	153 B

Dimensions International Standard

Section Width (mm)	410
Overall Diameter (mm)	835
Static Loaded Radius (mm)	350
Rolling Circumference (mm)	2513
SRI (mm)	400
Rim Rec	AG 11.75
ECE	E11-106R-005024

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.6
From 10 to 50	1025	1345	1630	1890	2175	2465	2655	2910	3195	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..