

AW 729 - Specifiche tecniche



Description

AW 729 è uno pneumatico agricolo specificatamente progettato per applicazioni di trasporto, lavorazione del terreno e raccolta e pressatura del fieno. La spalla arrotondata e il design del battistrada a tre scanalature centrali garantiscono una ridotta compattazione del suolo ed evitano danni al terreno.

AW 729 è lo pneumatico ideale per le esigenze dell'agricoltura moderna ed è adatto all'utilizzo sia su strada che fuori strada.

UM

International Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	385
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2560
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E11-106R-008727

Load capacity (Kg)

km/h / bar	2.60
10 FR	2970
25 FR	2520
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 09:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..