

AW 729 - Specifiche tecniche



Description

AW 729 è uno pneumatico agricolo specificatamente progettato per applicazioni di trasporto, lavorazione del terreno e raccolta e pressatura del fieno. La spalla arrotondata e il design del battistrada a tre scanalature centrali garantiscono una ridotta compattazione del suolo ed evitano danni al terreno.

AW 729 è lo pneumatico ideale per le esigenze dell'agricoltura moderna ed è adatto all'utilizzo sia su strada che fuori strada.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8

Dimensions US Standard

Usa code	94074150
Ply Rating	10
Section Width (inch)	15.2
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	100.8
Rim Rec	13.00
Rim Alt	13 ; W 13
ECE	E11-106R-008727

Load capacity (lbs)

mph / psi	38
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4680
5 DW	4630
15 DW	3940
20 DW	3700
25 DW	3300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..