

AW 909 - Specifiche tecniche



Description

AW 909 è stato sviluppato per la lavorazione della terra nonché le applicazioni di raccolta del fieno e di trasporto con attrezzi agricoli, rimorchi e presse per balle di fieno. Lo pneumatico è ideale per l'impiego nell'agricoltura moderna sia su strada che fuori strada.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS FREE ROLLING	131 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	300
Overall Diameter (mm)	844
Static Loaded Radius (mm)	370
Rolling Circumference (mm)	2473
Rim Rec	9.00
ECE	E4-106R-001893

Load capacity (Kg)

km/h / bar	3.40
10 FR	2730
25 FR	2320
30 FR	2185
40 FR	1950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..