

BK 823 - Scheda tecnica



Description

BK 823 è uno pneumatico progettato per trattori, attrezzi agricoli e rimorchi nelle applicazioni di lavorazione del terreno e di trasporto sia su campo che su strada. Lo speciale disegno a blocchi del battistrada, lo rende particolarmente idoneo per impieghi pesanti in cui ottime prestazioni di sterzata sono un requisito essenziale. È disponibile anche una versione HD con resistenza a tagli e lacerazioni avanzate.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Trattore • Rimorchio

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	94049202	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-004338
9.00 - 16	STANDARD	94042432	124 A8	12	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003603
9.00 - 16	STANDARD	94040131	127 A8	14	6.5		9.6	35.1	15.5	101.7	TT	E11-106R-003604
9.00 - 16	STANDARD	94060252	121 A8	10	6.5		9.6	35.1	15.5	101.7	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..