

BK 826 - Scheda tecnica



Description

Il pneumatico BK 826 è sapientemente progettato per i rimorchi nelle applicazioni di trasporto, offrendo durata e prestazioni senza pari. La versione "Harvester Special" è realizzata appositamente per la raccolta, garantendo un'affidabilità ottimale sul campo. Questo pneumatico diagonale vanta una carcassa rinforzata, che offre un'eccezionale capacità di carico per soddisfare le esigenze delle attività pesanti. Inoltre, il BK 826 è disponibile in una variante "Industriale", progettata con una resistenza al taglio e ai trucioli superiore, che lo rende la scelta ideale per le terre in condizioni difficili.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Mietitrebbia • Rimorchio

Industriale: Terna • Rimorchio

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
8.25 - 16	INDUSTRIAL	94048274		16	6.50 H	6.00 G	9.4	34	TT	
8.25 - 16	INDUSTRIAL	94049707		18	6.50 H	6.00 G	9.4	34	TT	
8.25 - 16	STANDARD	94034451		14	6.50 H	6.00 G	9.4	34	TT	E4-54R-0024095
8.25 - 16	STANDARD	94034468		16	6.50 H	6.00 G	9.4	34	TT	E4-54R-0024096
8.25 - 16	STANDARD	94034475		18	6.50 H	6.00 G	9.4	34	TT	E4-54R-0024097
8.25 - 16	STANDARD	94013289		8	6.50 H	6.00 G	9.4	34	TT	
8.25 - 16	TRACTOR TRAILER	94045518	134 A8	16	6.50 H	6.00 G	9.4	34	TT	
9.00 - 16	HARVESTER SPECIAL	94054879		12	6.50 H	6.00 G	10.4	36.4	TT	
9.00 - 16	HARVESTER SPECIAL	94070404		16	6.50 H	6.00 G	10.4	36.4	TT	
9.00 - 16	INDUSTRIAL	94029068		16	6.50 H	6.00 G	10.4	36.4	TT	E11-106R-004119
9.00 - 16	STANDARD	94013371		16	6.50 H	6.00 G	10.4	36.4	TT	E11-106R-004613
9.00 - 16	STANDARD	94030125		18	6.50 H	6.00 G	10.4	36.4	TT	
9.00 - 16	STANDARD	94026814		12	6.50 H	6.00 G	10.4	36.4	TT	
9.00 - 16	STANDARD	94013357		14	6.50 H	6.00 G	10.4	36.4	TT	
9.00 - 16	STUBBLE RESISTANT	94013449		16	6.50 H	6.00 G	10.4	36.4	TT	
9.00 - 16	TRACTOR TRAILER	94047017	138 A6	18	6.50 H	6.00 G	10.4	36.4	TT	E11-106R-005356
9.00 - 16	TRACTOR TRAILER	94062164	138 A8	18	6.50 H	6.00 G	10.4	36.4	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..