

BK-LOADER 53 - Specifiche tecniche



Description

BK-LOADER 53 è uno pneumatico con cinture in aramide sviluppato per pale caricatori in applicazioni industriali. Lo speciale disegno del battistrada garantisce ottima stabilità laterale oltre a straordinaria resistenza all'usura, a tagli e perforazioni grazie al battistrada extra profondo. BK-LOADER 53 si distingue per le eccezionali proprietà di autopulitura nonché grip e trazione eccellenti su superfici bagnate e asciutte. Lo pneumatico è particolarmente idoneo per operazioni di recycling.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Pala caricatrice

| | |
|-----------|---------------|
| Version | ARAMID BELTED |
| Type | TL |
| Tyre Size | 405/70 R 20 |
| LI/SS | 155A2/151A4 |

Dimensions International Standard

| | |
|----------------------------|-------------------------|
| Section Width (mm) | 407 |
| Overall Diameter (mm) | 1097 |
| Static Loaded Radius (mm) | 511 |
| Rolling Circumference (mm) | 3339 |
| SRI (mm) | 525 |
| Rim Rec | 13 |
| Rim Alt | 14 ; 13 SDC; 12 ;12 SDC |

Load capacity (Kg)

| km/h / bar | 1.5 | 2.0 | 2.5 | 3.0 | 3.5 | 4.0 | 4.5 | 5.0 | 5.5 |
|--------------|------|------|------|------|------|------|------|------|------|
| 20 TRANSPORT | 1210 | 1520 | 1805 | 2090 | 2375 | 2640 | 2905 | 3170 | 3450 |
| 10 LOADING | 1375 | 1725 | 2050 | 2375 | 2700 | 3000 | 3300 | 3600 | 3875 |
| Static | 2200 | 2750 | 3275 | 3800 | 4325 | 4800 | 5300 | 5750 | 6200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 02:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..