

COMMANDER 3 RIB - Specifiche tecniche



Description

COMMANDER 3 RIB è uno pneumatico anteriore con nervatura del battistrada a 3 costole sviluppato per la lavorazione del terreno e le operazioni di trasporto. Lo pneumatico garantisce eccellente durabilità ed elevata capacità di carico grazie alla distribuzione del carico ottimizzata sulle costole nella parte centrale e nell'area della spalla. La carcassa robusta e la miscola resistente a tagli e lacerazioni assicurano straordinaria resistenza alla perforazione.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricoltura: Trattore 2WD

Version	STANDARD
Type	TT
Tyre Size	6.50 - 16
LI/SS	98 A6

Dimensions International Standard

Ply Rating	8
TKPH	1
Section Width (mm)	183
Overall Diameter (mm)	765
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F ; 5.50 F
ECE	E11-106R-008288
TRA Code	F2

Load capacity (Kg)

km/h / bar	4.20
30	750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..