

EARTHMAX CRUSHER HAUL - Specifiche tecniche



Description

EARTHMAX CRUSHER HAUL è uno pneumatico radiale All Steel progettato per applicazioni di trasporto sia su strada che fuori strada nonché per operazioni nelle miniere. Lo pneumatico si distingue per la sua straordinaria durabilità e un ottimo chilometraggio oltre all'elevata capacità di carico grazie alla robusta costruzione e carcassa con cinture in acciaio. Il disegno del battistrada a forma di blocchi garantisce trazione eccellente. Inoltre, EARTHMAX CRUSHER HAUL offre eccellente comfort di guida e manovrabilità superiore oltre a ridurre l'affaticamento del guidatore.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Carro con cassone ribaltabile

Version	STANDARD
Type	TT
Tyre Size	11.00 R 20
LI/SS	152/149 J

Dimensions US Standard

Usa code	94070565
Ply Rating	18
Overall Width (inch)	11.4
Overall Diameter (inch)	43.4
Rim Rec	8.00
Rim Alt	8.50
Tread Depth	25

Load capacity (lbs)

mph / psi	120
62 Load Single	7825
62 Load Dual	7165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/05/2025 22:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..