

EARTHMAX CRUSHER HAUL - Scheda tecnica



Description

EARTHMAX CRUSHER HAUL è uno pneumatico radiale All Steel progettato per applicazioni di trasporto sia su strada che fuori strada nonché per operazioni nelle miniere. Lo pneumatico si distingue per la sua straordinaria durabilità e un ottimo chilometraggio oltre all'elevata capacità di carico grazie alla robusta costruzione e carcassa con cinture in acciaio. Il disegno del battistrada a forma di blocchi garantisce trazione eccellente. Inoltre, EARTHMAX CRUSHER HAUL offre eccellente comfort di guida e manovrabilità superiore oltre a ridurre l'affaticamento del guidatore.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Carro con cassone ribaltabile

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
10.00 R 20	STANDARD	94070558	149/146 J	7.50	8.00	10.7	41.9	0	0	TT	25
11.00 R 20	STANDARD	94070565	152/149 J	8.00	8.50	11.4	43.4	0	0	TT	25
12.00 R 24	STANDARD	94075959	160/156 K	8.50	9.00	12.2	48.4	22.2	149	TT	26
12.00 R 24	STANDARD	94075966	160/156 K	8.50	9.00	12.2	48.4	22.2	149	TL	26

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/05/2025 23:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..