

## EARTHMAX SR 22 - Specifiche tecniche



### Description

EARTHMAX SR 22 (G-2/L-2) è uno pneumatico radiale All Steel particolarmente progettato per motolivellatrici e loader che operano in condizioni invernali estreme su neve o ghiaccio. Gli operatori apprezzeranno l'eccellente trazione e la straordinaria stabilità garantite dal disegno del battistrada largo e non-direzionale.

### UM

International Standard

### Construction



RADIAL

### Machinery

Industriale: Dozer • Motolivellatrice • Pala caricatrice  
OTR: Dozer • Motolivellatrice • Pala caricatrice

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 15.5 R 25              |
| LI/SS     | 146 A8/169 A2          |

# Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| Overall Width (mm)         | 385       |
| Overall Diameter (mm)      | 1275      |
| Static Loaded Radius (mm)  | 557       |
| Rolling Circumference (mm) | 3841      |
| Rim Rec                    | 12.00/1.3 |
| Star Rating                | *         |
| TRA Code                   | G2/L2     |
| Tread Depth                | 28        |

## Load capacity (Kg)

| km/h / bar | 1.25 | 1.50 | 1.75 | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 40         | 1550 | 1750 | 2000 | 2180 | 2360 | 2575 | 2800 | 3000 | -    | -    | -    | -    | -    |
| 10         | -    | -    | -    | -    | -    | -    | -    | -    | 5000 | 5150 | 5450 | 5600 | 5800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..