

EARTHMAX SR 23 - Scheda tecnica



Description

EARTHMAX SR 23 (G-2/L-2) è uno pneumatico radiale All Steel particolarmente progettato per motolivellatrici e loader. Si distingue per l'eccellente trazione anteriore e laterale nonché per le proprietà eccezionali di autopulitura. La carcassa durevole e il battistrada particolarmente resistente ai tagli assicurano una lunga vita operativa.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Motolivellatrice • Pala caricatrice

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
15.5 R 25	CUT RESISTANT COMPOUND	94046829	G2/L2	*	146 A8/169 A2	12.00/1.3		15.1	49.8	22	147.9	TL	34
17.5 R 25	CUT RESISTANT COMPOUND	94060313	G2/L2	*	153 A8/176 A2	14.00/1.5		17.6	53	24.1	161.7	TL	34
20.5 R 25	CUT RESISTANT COMPOUND	94060603	G2/L2	*	161 A8/186 A2	17.00/2.0		21.1	58.7	26.3	176.7	TL	39

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..