

## EARTHMAX SR 25 PLUS - Specifiche tecniche



### Description

EARTHMAX SR 25 PLUS (G-2/L-2) è uno pneumatico radiale All Steel particolarmente progettato per motolivellatrici e loader che operano nelle applicazioni più dure nelle applicazioni di costruzione stradale e minerarie. Il disegno non direzionale del battistrada offre eccellenti proprietà di auto-pulitura insieme a ottime trazione e stabilità fuori strada.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriale: Dozer • Motolivellatrice • Pala caricatrice  
OTR: Dozer • Motolivellatrice • Pala caricatrice

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 14.00 R 24             |
| LI/SS     | 153 A8/175 A2          |

Dimensions US Standard

|                              |          |
|------------------------------|----------|
| Usa code                     | 94044962 |
| Overall Width (inch)         | 14.1     |
| Overall Diameter (inch)      | 54       |
| Static Loaded Radius (inch)  | 24.6     |
| Rolling Circumference (inch) | 163.2    |
| Rim Rec                      | 8.00TG   |
| Rim Alt                      | 9.00GR   |
| Star Rating                  | *        |
| TRA Code                     | G2/L2    |
| Tread Depth                  | 32       |

Load capacity (lbs)

| mph / psi | 29   | 33   | 36   | 40   | 44   | 47   | 51   | 54   | 76    | 80    |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 25        | 4940 | 5360 | 5840 | 6150 | 6600 | 7150 | 7400 | 8050 | -     | -     |
| 5         | -    | -    | -    | -    | -    | -    | -    | -    | 14800 | 15200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..