

EARTHMAX SR 315 - Specifiche tecniche



Description

EARTHMAX SR 315 è uno pneumatico radiale All Steel specificamente concepito e progettato per caricatori LHD. Offre prestazioni eccellenti nelle operazioni di scavo, caricamento e trasporto del carico nelle miniere sotterranee.

È dotato di una carcassa robusta, rinforzata da più cinghie d'acciaio, che riduce al minimo la rottura da impatto e le perforazioni da roccia. I fianchi robusti e le zone di rinforzo dell'EARTHMAX SR 315 garantiscono prestazioni eccellenti in ambienti rocciosi impegnativi, riducendo al minimo i tagli da roccia e i danni causati da sfregamento. Il battistrada liscio L-3S riduce il rischio di perforazione da rocce e pietre.

Il composto dell'EARTHMAX SR 315 è specificamente progettato per assicurare una bassa generazione di calore e affidabilità di servizio in miniere sotterranee.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Pala LHD

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 29
LI/SS	217 A2

Dimensions US Standard

Usa code	94070787
Overall Width (inch)	28.5
Overall Diameter (inch)	73.4
Static Loaded Radius (inch)	32.7
Rolling Circumference (inch)	221.9
Rim Rec	22.00/3.0
Star Rating	***
TRA Code	L3S
Tread Depth	55

Load capacity (lbs)

mph / psi	98	102	105	109	112	116
5	44100	45400	46700	48100	49400	50700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..