

## EARTHMAX SR 315 - Scheda tecnica



### Description

EARTHMAX SR 315 è uno pneumatico radiale All Steel specificamente concepito e progettato per caricatori LHD. Offre prestazioni eccellenti nelle operazioni di scavo, caricamento e trasporto del carico nelle miniere sotterranee.

È dotato di una carcassa robusta, rinforzata da più cinghie d'acciaio, che riduce al minimo la rottura da impatto e le perforazioni da roccia. I fianchi robusti e le zone di rinforzo dell'EARTHMAX SR 315 garantiscono prestazioni eccellenti in ambienti rocciosi impegnativi, riducendo al minimo i tagli da roccia e i danni causati da sfregamento. Il battistrada liscio L-3S riduce il rischio di perforazione da rocce e pietre.

Il composto dell'EARTHMAX SR 315 è specificamente progettato per assicurare una bassa generazione di calore e affidabilità di servizio in miniere sotterranee.

### UM

International Standard

### Construction



RADIAL

### Machinery

OTR: Pala LHD

| SIZE      | Version                | TRA Code | Star R | LI/SS  | RIM REC   | RIM ALT | OW  | OD   | SLR | RC   | Type | Tread Depth |
|-----------|------------------------|----------|--------|--------|-----------|---------|-----|------|-----|------|------|-------------|
| 26.5 R 29 | CUT RESISTANT COMPOUND | L3S      | **     | 211 A2 | 22.00/3.0 |         | 725 | 1865 | 830 | 5635 | TL   | 44          |
| 26.5 R 29 | CUT RESISTANT COMPOUND | L3S      | ***    | 217 A2 | 22.00/3.0 |         | 725 | 1865 | 830 | 5635 | TL   | 44          |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..