

EARTHMAX SR 33 PLUS - Specifiche tecniche



Description

Earthmax SR 33 PLUS è uno pneumatico radiale con un disegno a blocchi multipli che è stato progettato per garantire eccellente galleggiamento su superfici morbide, sabbiose e fangose. La carcassa All Steel si distingue per l'eccellente durabilità e la resistenza contro tagli e perforazioni. Earthmax SR 33 offre proprietà di autopulitura straordinarie nonché stabilità superiore.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	16.00 R 20
LI/SS	173/170 G

Dimensions US Standard

Usa code	94064038
Overall Width (inch)	17.6
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	22.9
Rolling Circumference (inch)	156.5
Rim Rec	11.25
Rim Alt	10.00W, 10.0
ECE	E11-54R-0017916

Load capacity (lbs)

mph / psi	110
56	14330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 14:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..