

EARTHMAX SR 33 - Specifiche tecniche



Description

Earthmax SR 33 è uno pneumatico radiale per veicoli universali. Il particolare disegno a blocchi è stato progettato per garantire eccellente trazione su superfici morbide, sabbiose o fangose. Earthmax SR 33 offre ottima stabilità oltre a proprietà di autopulitura straordinarie. La carcassa All Steel si distingue per l'eccellente durabilità e la resistenza contro tagli e forature.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	365/80 R 20 (14.5 R 20)
LI/SS	152 K

Dimensions International Standard

Overall Width (mm)	360
Overall Diameter (mm)	1096
Static Loaded Radius (mm)	496
Rolling Circumference (mm)	3318
Rim Rec	11
ECE	E11-54R-0017314

Load capacity (Kg)

km/h / bar	6.20
110	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 12:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..